

Packaging — Complete, filled transport packages and unit loads — Stacking tests using a static load

The European Standard EN ISO 2234:2002 has the status of a
British Standard

ICS 55.180.40

National foreword

This British Standard is the official English language version of EN ISO 2234:2002. It is identical with ISO 2234:2000. It supersedes BS EN 22234:1993 which is withdrawn.

The UK participation in its preparation was entrusted by Technical Committee PKW/1, Packaging generalities, to Subcommittee PKW/1/4, Packaging generalities – Test methods, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this subcommittee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the *BSI Catalogue* under the section entitled “International Standards Correspondence Index”, or by using the “Search” facility of the *BSI Electronic Catalogue* or of British Standards Online.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

This British Standard, having been prepared under the direction of the Consumer Products and Services Sector Policy and Strategy Committee, was published under the authority of the Standards Policy and Strategy Committee on 3 October 2002

Summary of pages

This document comprises a front cover, an inside front cover, the EN ISO title page, the EN ISO foreword page, the ISO title page, pages ii to iv, pages 1 to 4, the Annex ZA page and a back cover.

The BSI copyright date displayed in this document indicates when the document was last issued.

Amendments issued since publication

Amd. No.	Date	Comments

EUROPEAN STANDARD

EN ISO 2234

NORME EUROPÉENNE

EUROPÄISCHE NORM

September 2002

ICS 55.180.40

Supersedes EN 2234:1992

English version

Packaging - Complete, filled transport packages and unit loads - Stacking tests using a static load (ISO 2234:2000)

Emballages - Emballages d'expédition complets et pleins
et charges unitaires - Essais de gerbage utilisant une
charge statique (ISO 2234:2000)

Verpackung - Versandfertige Packstücke und
Ladeeinheiten - Stapelprüfung unter statischer Last (ISO
2234:2000)

This European Standard was approved by CEN on 30 August 2002.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Foreword

The text of the International Standard from Technical Committee ISO/TC 122 "Packaging" of the International Organization for Standardization (ISO) has been taken over as a European Standard by Technical Committee CEN/TC 261 "Packaging", the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by March 2003, and conflicting national standards shall be withdrawn at the latest by March 2003.

This document supersedes EN 22234:1992.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

Endorsement notice

The text of the International Standard ISO 2234:2000 has been approved by CEN as a European Standard without any modifications.

NOTE Normative references to International Standards are listed in annex ZA (normative).

INTERNATIONAL
STANDARD

ISO
2234

Third edition
2000-03-01

**Packaging — Complete, filled transport
packages and unit loads — Stacking tests
using a static load**

*Emballages — Emballages d'expédition complets et pleins et charges
unitaires — Essais de gerbage utilisant une charge statique*



Reference number
ISO 2234:2000(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 2234 was prepared by Technical Committee ISO/TC 122, *Packaging*, Subcommittee SC 3, *Performance requirements and tests for means of packaging, packages and unit loads (as required by ISO/TC 122)*.

This third edition cancels and replaces the second edition (ISO 2234:1985), which has been technically revised.

Introduction

It is the responsibility of the user of this International Standard to establish appropriate health and safety practice in accordance with relevant legislation.

Packaging — Complete, filled transport packages and unit loads — Stacking tests using a static load

1 Scope

This International Standard specifies three methods for carrying out a stacking test on a complete, filled transport package, or on a unit load, using a static load. Whichever method is employed, the test may be used to assess the performance of a package or a unit load, in terms of its strength or the protection that it offers to its contents when it is subjected to stacking. It may be performed either as a single test to investigate the effects (deformation, creep, collapse or failure) of stacking or as part of a sequence of tests designed to measure the ability of a package or a unit load to withstand a distribution system that includes a stacking hazard.

The test may also be used to investigate performance under particular conditions of loading, as, for example, when the bottom package in a stack rests on an open-decked pallet; or when the profile of the superimposed load is eccentric, as when it is supported on the bearers of a single-decked pallet which rests on a container. For such purposes, one of the three methods of carrying out the test may be more suitable than the others.

NOTE A method for carrying out a stacking test using a compression tester is given in ISO 12048¹⁾.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 2206, *Packaging — Complete, filled transport packages — Identification of parts when testing.*

ISO 2233, *Packaging — Complete, filled transport packages and unit loads — Conditioning for testing.*

3 Term and definition

For the purposes of this International Standard, the following term and definition applies.

3.1 test item

a complete filled transport package or unit load

1) ISO 12048, *Packaging — Complete, filled transport packages — Compression and stacking tests using a compression tester.*

4 Principle

The test item is placed on a flat, horizontal surface and subjected to an evenly distributed load applied from above, using one of three methods. The load, atmospheric conditions, period of time under load and attitude of the test item are predetermined.

NOTE The top-to-bottom or the side-to-side deflection of the test item during the test may be measured, if appropriate.

5 Apparatus

5.1 Horizontal surface, which is flat (the difference in height between the highest and lowest points not exceeding 2 mm) and rigid. A concrete floor at least 150 mm thick is suitable.

5.2 Means of loading, which, according to the method chosen (1, 2 or 3) is as described in 5.2.1 to 5.2.3.

5.2.1 Method 1: stack of test items, each item being identical with the item under test. The number of test items is such that their total mass forms an appropriate load.

5.2.2 Method 2: loading platform, free to tilt to an equilibrium position on the test item, together with an appropriate load.

The loading platform, when placed centrally on top of the test item, shall be large enough to extend at least 100 mm over all sides of the top surface of the test item and rigid enough to support the load completely without deformation.

NOTE This type of load is sometimes referred to as "free load".

5.2.3 Method 3: loading platform, such that the lower surface of the platform is constrained to remain horizontal, together with an appropriate load.

The loading platform, when placed centrally on top of the test item, shall be large enough to extend at least 100 mm over all sides of the top surface of the test item and rigid enough to support the load completely without deformation.

NOTE 1 This type of load is sometimes referred to as a "guided load".

NOTE 2 If guides are used to ensure that the loading platform remains horizontal, they should not cause friction that could affect the test results.

5.3 Means of measuring deflection (if necessary), accurate to ± 1 mm and capable of indicating either an increase or a decrease in dimensions. In addition, the apparatus shall meet the requirements and tolerances of clause 8.

NOTE Stable and safe loading during the test is dependent on the friction between the top surface of the test item and the bottom surface of the loading platform, as well as the ability of the test item to resist deformation. Means therefore, should be provided to produce a stable test assembly and to ensure that, if failure occurs, the load is restrained and does not cause danger to personnel in the vicinity.

6 Test item preparation

Fill the test item with its intended contents and ensure that it is closed normally, as if ready for distribution.

NOTE Simulated or substituted contents may be used, on condition that the dimensions and physical properties of such contents should be as close as possible to those of the intended contents. However, the closure should be the same as for distribution.

7 Conditioning

The test item shall be conditioned in accordance with one of the conditions described in ISO 2233.

8 Procedure

8.1 Wherever possible the test shall be carried out in atmospheric conditions identical to those used for conditioning, and particularly where this is critical to the materials or application of the test item. In other circumstances, the test shall be carried out in atmospheric conditions which approximate those used for conditioning, as closely as is practicable.

8.2 Position the stack of test item (5.2.1) or, alternatively, the loading platform (5.2.2 or 5.2.3) centrally over the test item which has been placed on the flat, horizontal surface (5.1).

8.2.1 If methods 2 and 3 are being used, place the masses making up the load on the loading platform without impact, ensuring that they are in full contact with the loading platform before being released. The masses shall be distributed uniformly over that portion of the surface of the loading platform in direct contact with the test item to ensure that the centre of gravity of the load is immediately above the centre of the top surface of the test item. The mass of the total load, including the mass of the loading platform, shall be within 2 % of the predetermined value. The distance of the centre of gravity of the load above the loading platform shall not exceed 50 % of the height of the test item.

8.2.2 In methods 2 and 3, if measurements are taken, this shall be done between the two surfaces exerting compression on the test item after the application of a pre-load sufficient to assure a good contact between the loading platform and the test item.

8.3 Apply the load for the required period of time (usually 24 h, according to the material) or until collapse.

8.4 Remove the load and examine the test item.

NOTE 1 At any time during the test it may be necessary to measure dimensions.

NOTE 2 Appropriately profiled inserts to represent particular loading conditions may be placed above or below the test item or both above and below, as required.

NOTE 3 In the case of test items stored on pallets or in stacks, the test should be carried out on several test items side by side or using an actual stacking pattern.

9 Test report

The test report shall include:

- a) a reference to this International Standard;
- b) the name and address of the testing laboratory and the name and address of the customer;
- c) a unique identification of the report;
- d) the date of receipt of the test items and the date(s) of performance of the test;
- e) the name, title and signature of persons accepting test responsibility for the test report;
- f) a statement to the effect that the test results relate only to the items tested;

- g) a statement that the report shall not be reproduced except in full without the written approval of the testing laboratory;
- h) the number of replicate test items tested;
- i) a full description, including dimensions, structural and material specifications of the test item and its fittings, cushioning, blocking, closure or reinforcing arrangements, gross mass of the test item and mass of the contents in kilograms;
- j) a description of contents, if simulated or substituted contents were used, full details shall be given;
- k) the relative humidity, temperature and the time of conditioning; the temperature and relative humidity of the test area at the time of test; whether these values comply with the requirements of ISO 2233;
- l) the attitudes in which the test item was tested, using the method of identification given in ISO 2206;
- m) the mass, in kilograms, of the total load, including the mass of the loading platform, and the period of time during which the test item was under load, the means of loading used, i.e. method 1, 2 or 3, whether guides were used, and if so, their design; the test item pattern under test;
- n) the location of deflection measurement points on the test item and the stage of test at which deflection measurements were made;
- o) the design and dimensions of any profiles used;
- p) the type of apparatus used;
- q) any deviations from the test methods described in this International Standard;
- r) a record of the results, including observations which assist in the correct interpretation of the results.

Annex ZA
(normative)

**Normative references to international publications
with their relevant European publications**

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies (including amendments).

NOTE Where an International Publication has been modified by common modifications, indicated by (mod.), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN</u>	<u>Year</u>
ISO 2206	1987	Packaging - Complete, filled transport packages - Identification of parts when testing	EN 22206	1992
ISO 2233	2000	Packaging - Complete, filled transport packages and unit loads - Conditioning for testing	EN ISO 2233	2001

BSI — British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover.
Tel: +44 (0)20 8996 9000. Fax: +44 (0)20 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: +44 (0)20 8996 9001.
Fax: +44 (0)20 8996 7001. Email: orders@bsi-global.com. Standards are also available from the BSI website at <http://www.bsi-global.com>.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre.
Tel: +44 (0)20 8996 7111. Fax: +44 (0)20 8996 7048. Email: info@bsi-global.com.

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration.
Tel: +44 (0)20 8996 7002. Fax: +44 (0)20 8996 7001.
Email: membership@bsi-global.com.

Information regarding online access to British Standards via British Standards Online can be found at <http://www.bsi-global.com/bsonline>.

Further information about BSI is available on the BSI website at <http://www.bsi-global.com>.

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

Details and advice can be obtained from the Copyright & Licensing Manager.
Tel: +44 (0)20 8996 7070. Fax: +44 (0)20 8996 7553.
Email: copyright@bsi-global.com.